


## Electro-Voice®

a MARK IV company

600 Cecil Street Buchanan, Michigan 49107 Phone: 616-695-6831 FAX: 616-695-1304

## SERVICE DATA

## Model FR12-2B



Specifications: FR12-2B Model & Spec: 1013-2163

Frequency Response,

(-3-dB): 80-18,000 Hz (-10-dB): 50-20,000 Hz

Power Handling,

Long-Term: 100 W

SPL at 1 Watt/1 Meter: 96 dB

Nominal Impedance: 8 ohms


Minimum Impedance: 6.5 ohms


Nominal Dispersion (h/v): 60° x 60°


Crossover Frequency: 1,500 Hz

Dimensions (hwd): 25.5 in. x 16.5 in. x 8.8 in.


Weight: 46 lb







)NE KIT EV# 82812 XX : WOOFER



29	42730	1	CAPACITOR, 4.3 ± 10%, 100 V
28	35027	1	INDUCTOR, 0.26 mH
27	3584	1	INDUCTOR, 0.73 mH
26	A27323	1	TERMINAL STRIP
25	63037-CP	2	SCR, #8-15 X 1/4 IN., HEX WSHR HD, BLK
24	46671	1	RESISTOR, 2.0 OHMS ± 10%
23	42711	1	CAPACITOR, 18 MFD ± 15%, 70 V MYLAR
22	35034	1	INDUCTOR, 1.6 mH
21	82727	1	CROSSOVER S/A
20	38768	4	WASHER, COUNTERSUNK, BLACK NYLON
19	62986-CP	4	SCREW, #8-18 X 11/2 IN., FLAT HD, BLK
18	82749	1	INPUT PANEL S/A
17	70809	1	SCREEN, TWEETER, SCOTTFOAM, CHARCOAL
16	82697	1	ENCLOSURE S/A
15	610224	4	SCREW, 1/4—20 X 1 IN., HEX WSHR HD, SLT'D, GD#5 STL, BLK ZINC
14	89545	1	11/2 IN. DOME LOUDSPEAKER
13	63069-CP	2	SCREW, #8—18 X 5/8 IN., PAN HD, X-REC, TYPE AB, STL, BLK ZINC
12	63056-CP	4	SCREW, #8—15 X 1 IN., FLAT HD, X-REC, TYPE A, STL, BLK ZINC
11	63053-CP	3	SCREW, #8 X 5/8 IN., HEX WSHR HD, TRI LOBULAR, STL, BLK ZINC
10	48994	1	NAMEPLATE
9	38722	1	GASKET, 2.94 OD X 1.58 ID X .25 THICK, CLOSED CELL FOAM
8	70921-UP	1	HORN, 8 IN. DIRECTOR, PLASTIC, BLK
7	28039-62	1	TAPE, FOAM, TESIMOL, 39 IN. LONG
6	28039-40	1	TAPE, FOAM, TESIMOL, 351/2 IN. LONG
5	63075-CP	8	SCREW, #8—15 X 3/4 IN., OVAL HD, X-REC, BLK ZINC
4	20745-AE	1	NUT, PUSH, PALNUT PS125006, ZINC PLT
3	20354	18	PLUG, HOLD, Ø5/16, NYLON, BLACK, HEYCO P/N 2613
2	19086	1	SPRING, SPIROL
_		1	
1	1812-0560	1	LOUDSPEAKER, 12 INCH

## FINAL ASSEMBLY PARTS LIST

